



## D952HD

Mobilní projektor



### Universální využití HD rozlišení

Rozlišení Full HD 1080p s působivou barevnou reprodukcí, úžasným výkonem a snadnou integrací je Vivitek D952HD schopen zajistit působivé prezentace v plném HD rozlišení. Tento univerzální projektor boří hranice mezi projekcí filmů a prezentací. Světelný výkon 3000 ANSI Lm a kontrastní poměr 3000:1 spolu s DLP® a BrilliantColor™ technologií dokáže zajistit efektivní dojem z prezentace obsahu s vysokým rozlišením.

#### Vlastnosti:

Rozlišení Full HD 1920 x 1080

Světelný výkon 3500 ANSI Lm,  
 kontrastní poměr 3000:1

Technologie VividWheel III pro zvýšení  
 kvality barevné reprodukce

Vstup HDMI v1.3

Lampa s prodlouženou životností  
 až 4000 hodin (v eco modu)

DLP® and BrilliantColor™ technologie  
 od Texas Instruments

Možnost uzamčení ovládacího panelu  
 brání nechtěné změně nastavení

Kryt lampy na vrchní straně projektoru  
 pro snadný přístup

Specifications	
Brightness	3500 Lumens (typical)
Native Resolution	1080p (1920 x 1080)
Contrast Ratio	3000:1 (Full On/Off)
Lamp Life and Type	~4000/3000 Hours (Standard/Boost Mode), 280W
Lamp Part #	1BA
Display Type	Single 0.65" DLP® Technology by Texas Instruments
Throw Ratio	1.6 to 1.92:1 (Distance/Width)
Image Size (Diagonal)	23.5" to 282.3" (0.6 to 7.2 m)
Projection Distance	3.3' to 32.8' (1.0 to 10.0 m)
Projection Lens	F=2.5, f=23.5-28.2mm
Zoom Ratio	1.2:1 Manual Zoom/Focus
Aspect Ratio	16:9 Native, 4:3 Compatible
Offset	130%
Keystone Correction	+15° Vertical
Color Spectrum	16.7 Million
Horizontal Scan Rate	15, 30 to 90 KHz
Vertical Scan Rate	43 to 85 Hz
Speaker	5W Mono
Remote Control	Fully Featured IR Remote with Laser Pointer and Mouse
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Uniformity	85%
Computer Compatibility	1080p, WSXGA, UXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV (576i), EDTV (480p, 576P), HDTV (720p, 1080i), NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM
I/O Connection Ports	HDMI v1.3 (x2), VGA-In, Composite Video, Component Video, S-Video, VGA-Out, RCA Audio-In, Mini-Jack Audio-In, Mini-Jack Audio-Out, RS-232c, RJ45, USB (Service)
Security	Kensington® Lock Port, Security Bar
Weight	7.5 lbs (3.4kg)
Dimensions (W x H x D)	13.1" x 4.4" x 10" (333 x 113 x 255 mm)
Noise Level	30dB/35dB (Standard/Boost Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 290w (Standard Mode), 350W (Boost Mode), <1W (Standby Mode)
Operating Temperature	41 to 104°F (5 to 40°C)
Warranty	1-Year Limited Warranty, 90-Day Lamp Warranty
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card
Optional Accessories	Replacement Lamp, Remote, Carrying Case
UPC	8 14964 33495 4

