



Vivitek D871ST

Velký obraz s krátkou projekční vzdáleností s 3D



Vlastnosti

- Nativní rozlišení XGA a schopnost zobrazení až UXGA (1600 x 1200)
- Ostrá a detailní kvalita obrazu s DLP® a BrilliantColor™ technologií
- Velký 82" obraz ze vzdálenosti pouze 1 metru
- Vysoký světelný výkon 3,000 ANSI Lm a kontrastní poměr 15,000:1
- Vysoce účinná lampa s životností až 6,000 hodin (ve Standard Mode)
- 3D-Ready podle DLP® Link™
- Rozšířené nastavení barev a zobrazení
- Snadný přístup ke krytu lampy na vrchní straně přístroje
- Utěsněný optický systém zabrání vniknutí prachu
- RJ45 síťové připojení pro integraci a správu systému
- 10W audio reproduktor

Fotky



Specifikace produktu

Display Type	DLP
Brightness	3000 ANSI Lumens
Native Resolution	XGA (1024 x 768)
Maximum Resolution	UXGA (1600 x 1200)
Contrast Ratio	15,000:1
Lamp Life and Type	4,500 /6,000 Hours (Boost/Std. Mode), 190W
Throw Ratio	0.6 (82" @ 1m)
Image Size (Diagonal)	41" - 328"
Projection Distance	0.5 - 4m (1.6ft to 13.1ft)
Projection Lens	F=2.7, f = 6.82mm
Zoom Ratio	Fixed Lens
Aspect Ratio	4:3 Native
Offset	128% +/-10%
Keystone Correction	Vertical +/- 40
Horizontal Frequency	15, 30-90 KHz
Vertical Scan Rate	43 - 85 Hz
Speakers	10W (Mono)
Lens Shift Range	N/A
Video Compatibility	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v1.3 (x2), VGA-In, S-Video, Composite Video, Audio-In RCA (L/R), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ45, RS-232C, Mini-USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (W x D x H)	285 x 261 x 121.8 mm (11.22" x 10.3" x 4.8")
Weight	2.7Kg (6 lbs)
Noise Level	32/35 db (Std. / Boost Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	240W (Boost Mode), 200W (Std. Mode), <0.5W (Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, Documentation Kit
Optional Accessories	Replacement Lamp, Remote, Carrying Case

